


Platform Scales



- Large backlit LCD display
- Simple 4 button operation
- Portable with battery power
- Kg/ lb/ oz/ lb & oz switchable
- Tare function
- Weighing
- Hold function
- RS-232 bi-directional interface
- Animal / dynamic weighing
- Stainless steel weighing pan with remote indicator
- Mains adapter and wall mounting kit supplied as standard



Model CPWplus 150

Readability 150Kgs @ 50grams

Technical Specifications

Models CPWplus: 35, 75, 150, 200

Maximum capacity: 35Kg, 75Kg, 150kg, 200Kg


Readability: 10, 20,50, 50g

Tare range: Full

Repeatability (S.D.): 50g

Linearity (±): 100g

Platform size: 300x300mm



General Specifications

Units of measurement: Kilogram (kg), Pound (lb), Pound-Ounce (lb-oz)

Typical stabilisation time: 2 Sec

Interface: RS-232 bi-directional Interface

Calibration: Automatic External with user selectable calibration mass

Display: LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together

Operating temperature: 0° - 40°C

Housing: Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform

Overall dimensions (WxDxH): 300x300x50mm

Power supply: 6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter

Net weight: 4kg

Key Accessories

- Hard Carry Case with Lock
- Thermal Printer
- Thermal Paper Roll for Printer
- RS-232 Cable
- DU - Data Collection Programme
- RS-232 Cable



We follow a policy of continuous improvement and reserve the right to change specifications without notice.